




Amik 312

Technical Specifications

- › **Structure**
 - Made of tubular and sheet steel, continuous wire arc welding
- › **Polypropylene**
 - Material:
 - For indoor use: Polypropylene copolymer IF-727
 - For outdoor use: Polypropylene copolymer IF-728 with additives for colour-stabilising and UV protection
 - Tensile strength according to ISO 527-2: 26 Mpa
 - Modulus of elasticity according to ISO 527-2: 1250 Mpa
- › **Paint**
 - Interior: Electrostatic polyester powder
 - Exterior: Electrostatic polyester powder (with electrolytic coating)
 - Paint thickness:
 - Interior: 70-80 microns.
 - Exterior: 90-100 microns.
- Adhesion by grid according to UNE-EN ISO 2409 : 100%.
- › **Classification of resistance and durability:**
 - UNE-EN 12727 Level 4 (Severe use).
- › **Fire resistance**
 - BS 5852. Clause 12. Ignition sources 0, 1 and 5 (with approved fabric)
 - USA: CAL T.B. 133 (with approved fabric).
- › **Weight:** 2082 gr.
- › **UV Guarantee:** 2 years.

General Dimensions



General Description

› Monoblock seat, with high performance and durability, and great versatility.

Designed for both outdoor and indoor use in stadiums, arenas, sports centers and sports facilities in general. Complies with the characteristics recommended by FIFA and other international sports federations.



• Thinner design than most similar seats., with no need for visible reinforcements, to achieve the necessary robustness.

Technical Specifications

• **Technology and finish.** Injection of moulded copolymer (PP), textured in soft acid mould, with anti-scratch treatment and prevention of dirt accumulation. Highly durable pigmented coloured plastic with colour stabilizing additive for UV protection.


The incorporation of IML technology allows the placement of club or entity logos on the surface during the thermoplastic forming process, ensuring unlimited life under any circumstance.

• **Security.** Fully rectangular rear geometry and minimization of the gap between seats.



• **Numbering .** The case has a small housing in the upper part of the backrest to accommodate a numbered plate, so that is embedded inside, preventing it from being stripped off. This system also provides optimum visibility of the seat number. Possibility of numbering on the front and rear parts.

Drainage system. Small hole in the seat surface for water drainage.



Installation features:

• **Fixing options.** The case can be fixed directly to the floor/stand, by means of rise fixing or on a beam with foot to the ground, depending on the characteristics of the installation.


• **Mod. 310 Stand fixation.** The seat is fixed directly to the stand by means of 4 anchor points on the upper part, sealed with plugs, providing a smooth seat surface.

Requirements: tier height between 43 and 45 cm. Optional support on stand that allows to raise the base of the seat by 10 cm. This support can be adapted to concrete, metal, wood, phenolic and ceramic stands. Please, check the most suitable anchorage depending on the surface.

• **Mod. 313 Free standing or on a beam rise mounted.** By means of a metal bracket to the wall of the support with 3 fixing points. The fixation of the support to the monocoque is on its lower part, leaving the visible part neat and without discontinuities.



The seat is fixed to 60x40mm rectangular steel profile by means of a fixing flange made of 4mm thick steel plate, which is attached to a lower base plate installed in the lower part of the seat. The system allows to easily remove or relocate each location.




The cutting of the metal supports by laser technology allows a precise design of them, according to the geometry of the bleachers.

Requirements: Minimum stand of 40cm up to any higher height, respecting the recommended height for ergonomic seating. This type of fixation is imperceptible to the user's sight.

Installation features:

• **Mod. 312 Fixation on a beam with base to the floor.** Suitable for any stand height. By means of a metal bracket to the wall of the support with three fixing points. The seat is fixed to a 60x40mm rectangular steel profile by means of a fixing flange made of 4mm thick steel sheet, which is attached to a lower sheet metal base installed on the underside of the seat. The system allows easy relocation and installation of each seat.

The support to the floor is a 60x40mm profile with a steel foot welded on its lower part, 8mm thick. The fixing to the floor is by means of 4 anchor points.



Materials and finishes

Colours for plastic parts

OUTDOOR

EXT-1015	EXT-8025	EXT-6029	EXT-1006	EXT-1003	EXT-1018	EXT-3020	EXT-5005	EXT-5000	EXT-7040
					SUPPORTS				
EXT-9016	EXT-9010	EXT-9005					Black 001		

* Opciones de color con protección UV/FR validadas con Xenotest. Consulte con nuestro equipo comercial otras opciones disponibles.

Colours for metallic parts

Sablé Black 900	Sablé Grey 150

No obstante, al objeto de facilitar al cliente las últimas novedades, FIGUERAS se reserva la facultad de introducir las modificaciones y variaciones que estime más adecuadas y convenientes para comercializar sus productos.